

A SOLUTION FROM THE GENIUS SERIE OF PRODUCTS



ELECTRICAL FAILURE MONITORING

SYSTEM

FIRE PREVENTION LEAKAGE CURRENT **TEMPERATURE**



24/7 MONITORING

Easy installation by a certified electrician

Independent system

Up to 64 reading points

Real time data

Customized report

No subscription required

Be notified!

certified (SP



Alerts of any electrical abnormalities detected by FarmGuard are sent via the FarmQuest service by text message and/or email.

The most critical alerts can also be transmitted via the telephone answering machine or via the customer's alarm system.

Adaptable to all buildings and all productions.

System self-validation. Any connection problem (internet, power supply, sensors, heat detectors) is reported.



ELECTRICAL FAILURE DETECTION AGRICULTURAL | COMMERCIAL | INDUSTRIAL

Monitoring of the total current leakage of the defective equipment and the temperature of the electrical components. Leakage current is due to a defective device, whereas overheating of an electrical panel is due to a faulty contact. In addition, FARMGUARD also supports heat detectors (optional).

Installation self-validation at building and system level

- High panel temperature versus room temperature
- Electrical panel leakage current (normal/abnormal)
- · Heat detector, probe and sensor (powered or not)
- Module and current sensor (powered or not)

WWW.MONITROL.COM